



#1 CHOICE OF PROFESSIONALS®

909 N. Sepulveda Blvd., Suite 650, El Segundo, CA 90245 310-955-9200

EMERGENCY TEL. NO.: (519) 882-2300

MATERIAL SAFETY DATA SHEET

WHMIS: Not controlled

I - PRODUCT INFORMATION

PRODUCT NAME	BAKOR BLUESKIN ROOF RF200
PRODUCT TYPE	SHEET MEMBRANE IN ROLL FORM
PRODUCT USE	SELF-ADHESIVE ROOFING UNDERLAY

II - HAZARDOUS INGREDIENTS

INGREDIENTS	%	CAS #	EXPOSURE LIMITS	LD50/LC50(SPECIES & ROUTE)
PETROLEUM ASPHALT	40 - 70	8052-42-4	5 mg/m ³ OSHA PEL	Not Available

III - PHYSICAL DATA

PHYSICAL STATE <input type="checkbox"/> GAS <input type="checkbox"/> LIQUID <input checked="" type="checkbox"/> SOLID	ODOR & APPEARANCE - slight petroleum odor Blue film top side, release film back side.	ODOR THRESHOLD (PPM) Not available	
VOLATILE (VOL.) 0%	VAPOR PRESSURE (mm Hg) Not applicable	VAPOR DENSITY (AIR = 1) Not applicable	EVAPORATION RATE (BuAc=1) Not applicable
BOILING POINT (°C) Initial : 370 °C	FREEZING POINT (°C) Not applicable	SPEC. GRAVITY (WATER - 1) 0.9 - 1.1	DENSITY (g / ml) 0.9 - 1.1
SOLUBILITY (IN WATER) INSOLUBLE	COEF. OF WATER/OIL DIST. Not available	pH Not applicable	

IV - FIRE & EXPLOSION HAZARD

FLAMMABILITY	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	CONDITIONS OF FLAMMABILITY	
		Not Applicable	
FLASH POINT (°C):	204°C Min.	FLAMMABLE LIMITS (% VOLUME)	
METHOD:	COC	LOWER:	N/A
		UPPER:	N/A
TDG FLAMMABILITY CLASS		SENSITIVITY TO MECHANICAL IMPACT	
NOT REGULATED		NONE	
		SENSITIVITY TO STATIC DISCHARGE	
		NONE	
HAZARDOUS COMBUSTION PRODUCTS	Primary combustion products are carbon monoxide, carbon dioxide, sulfur oxides and hydrogen sulfide. Other undetermined hydrocarbon fractions could be released in small quantities.		
MEANS OF EXTINCTION	Water fog, foam, CO2 or dry chemical.		
SPEC. FIRE FIGHTING PROCEDURES	Use water spray to cool fire-exposed containers. Self-contained breathing apparatus and full protective clothing should be worn when fumes or smoke are present.		

V - PREPARATION OF M.S.D.S.

PREPARED BY:	PHONE NUMBER	DATE
WHMIS Group	(519) 882-2300	APR. 06

VI - REACTIVITY DATA

CHEMICAL STABILITY	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	CONDITIONS TO AVOID:
		Not Applicable
INCOMPATIBILITY (SUBSTANCE TO AVOID)	Strong oxidizing agents may ignite the product.	
CONDITIONS OF REACTIVITY	Hot asphalt may splatter on contact with water.	
HAZARDOUS DECOMPOSITION PRODUCTS	Not applicable	

VII - TOXICOLOGICAL PROPERTIES

THRESHOLD LIMIT VALUE	LC50/LD50 (estimated)
5 mg/m3(OSHA-PEL) for asphalt fumes	Not Available
ROUTE OF ENTRY	<input checked="" type="checkbox"/> SKIN CONTACT <input type="checkbox"/> SKIN A <input checked="" type="checkbox"/> EYES <input checked="" type="checkbox"/> INGESTION <input checked="" type="checkbox"/> INHALATION
EFFECTS OF ACUTE EXPOSURE	Product not a problem in normal use. If burning Inhalation of fumes is irritating to eyes and respiratory tract.
EFFECTS OF CHRONIC EXPOSURE	Long-term skin contact can result in irritation, dermatitis and increased sensitivity to sun.
IRRITANCY	Fumes can be irritant to eyes and respiratory tract.
SENSITIZATION	After prolonged exposure to fumes
SYNERGISTIC MATERIALS	not available
<input type="checkbox"/> CARCINOGENICITY <input type="checkbox"/> REPRODUCTIVE EFFECTS <input type="checkbox"/> TERATOGENICIT <input type="checkbox"/> MUTAGENICITY	
no evidence that bitumen's are carcinogenic to humans	

VIII - FIRST AID MEASURES

SKIN	For cold product wash skin with soap and water.
EYES	Flush eyes thoroughly with plenty of lukewarm water. Get medical attention.
INHALATION	Remove victim to fresh air. If breathing is difficult, administer oxygen and get medical attention.
INGESTION	Ingestion is unlikely but if it happens do not induce vomiting. In general, no treatment is necessary unless large quantities are ingested, get medical advice.

IX - PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT	EYES: NONE
	GLOVES: Work gloves (loose), gauntlet style.
	CLOTHING: Long sleeved clothing recommended
	RESPIRATOR: None
ENGINEERING CONTROLS (VENTILATION, ETC.)	Not applicable
LEAK AND SPILL PROCEDURE	If product has been heated and released from solid form allow to cool and solidify. Break up and recover. Scoop into drums.
WASTE DISPOSAL	Bury in an approved landfill or burn in an improved incinerator as per local regulations.
HANDLING PROCEDURES	Keep material dry. Wood pallet and/or packaging should not be solely relied upon for safety when handling or hoisting material. Use proper equipment, hoisting and rigging techniques to stabilize material and follow all applicable construction safety guidelines and regulations when handling or hoisting material.
STORAGE REQUIREMENTS	Store in a dry, cool area protected from sun.
SHIPPING INFORMATION	None

While Henry Company believes that the data contained herein are factual & opinions expressed are those of qualified experts regarding the results of the tests conducted, the data is not to be taken as warranty or representation for which Henry Company assumes legal responsibility. These are offered solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with federal, provincial or municipal laws and regulations.