

# Blueskin<sup>®</sup> ROOF RF 200 Self-Adhered Roof Underlayment

## Physical Properties

- Color .....Blue	- Adhesion to Plywood .....5.0 lb./in (ASTM D903)
- Thickness .....40 mils	- Flexibility at -29°C .....Pass (ASTM D1970)
- Elongation at break .....100% (ASTM D1970)	- Water Vapor Transmission .....0.015 perms (ASTM E96)
- Tensile Strength .....600 psi min. Membrand (ASTM D412)	
- Maximum V.O.C. ....0 grams/liter	
- Flow @ 90°C .....None (ASTM D1970)	

## Packaging

- Thickness .....40 mils	- Gross Coverage .....225 ft <sup>2</sup>
- Roll Length .....75'	- Net Coverage .....207 ft <sup>2</sup>
- Roll Width .....36"	
- Top Surface.....Slip Resistant Film	
- Bottom Surface.....Siliconized Release Film	* Based on 2.75" laps both side and end.

## Description

Blueskin<sup>®</sup> ROOF RF 200 is an SBS modified bitumen membrane reinforced with a blue skid resistant polyethylene film. The membrane is specifically designed to be self-adhered on sloped roof surfaces.

## Features

- Self-sealing when penetrated by mechanical fasteners or nails.
- Fully adhered system prevents lateral moisture migration.
- Premium anti-skid surface for applicator safety.
- Split release backing for fast application.

## Uses

Blueskin<sup>®</sup> ROOF RF 200 is used as a self-adhered membrane designed to be adhered directly to roof decks or certain insulation panels prior to the application of finished roof coverings including shingles, cedar shakes or tile. Its main function is to serve as a secondary waterproofing layer, in both residential and commercial building, protecting the building's interior from damages caused by water infiltration as a result of ice dam formation and wind-driven rain.

## Limitations

Not resistant to oils and solvents. Not designed for permanent exposure. Good practice calls for the membrane to be covered as soon as practical. Provide adequate insulation and ventilation in cold climate areas. Thin films of dust, water, frost, or ice will affect the skid resistance of this product. Do not use in contact with flexible PVC (Poly Vinyl Chloride) membranes.

New dimensional lumber decks may contain knots with resin levels which can attack and severely soften the Blueskin<sup>®</sup> ROOF RF 200 bitumen compound. Henry will not be held responsible.

# Blueskin® ROOF RF 200 Self-Adhered Roof Underlayment

---

## Storage

---

Store rolls on end in original pallets or elevated platform. Protect from weather or store in a dry enclosed area not subject to heat over 120°F.

## Surface Preparation

---

Blueskin® ROOF RF 200 is designed to be adhered directly to the structural deck or to certain insulation panels such as polyisocyanurate. Acceptable substrates include plywood, OSB, wood plank, wood composition, concrete, gypsum board sheathing, glass faced gypsum sheathing, metal, and masonry.

All substrates are to be free of dust, oil, dirt, debris, and moisture. All protrusions must be removed to provide a smooth surface. On re-roofing applications, remove old shingles, nails, and other loose materials.

Priming is generally not required but is recommended over Dens Deck™, concrete or masonry substrates, or in cold weather. Prime with Aquaprime™, Aquatac™, or Blueskin® Primer applied as per application and handling guidelines outlined in specific data sheets. Allow primer to dry to a tacky film. Primed surfaces not covered by membrane during the same working day must be reprimed.

Note: Where furring strips or Z bars are installed immediately after installation of membrane, priming of substrate may be omitted.

## Application

---

Optimum adhesion is achieved when ambient and surface temperature are above 40°F. For installation below 40°F contact your Henry representative.

Apply membrane parallel or perpendicular to slope. When applied perpendicular to slope, apply membrane beginning at low point and proceed in shingle fashion. Position sheet to achieve correct overlap and alignment. Release upper half of release film by peeling off at 90° angle, then peel back second half of lower release film. Overlap on to clear film on sides and at ends a minimum of 2.75" for all applications.

**Roof Edge Applications:** When membrane is folded over the roof edge, it must be covered by flashing, gutter, or metal edge. Apply membrane far enough up the roof deck to meet local codes and to prevent leaks caused by ice dam formations.

**Ridge & Valley Applications:** Roll out and align manageable lengths of membrane. Slowly peel first half of release film. Press firmly in place beginning at centre of ridge or valley. Repeat with second half of release film. Overlap at ends and sides a minimum of 3". Apply in shingle fashion on valleys.

## Protection of Membrane

---

See limitations. Not designed for permanent exposure. Apply finish-covering materials as soon as practical following membrane application. When left exposed prior to application of finish covering, secure membrane in place with mechanical fasteners to protect against wind exposure and uplift. Protect membrane from excessive traffic during application and until final roof covering is in place.

## Limited Warranty

---

We, the manufacturer, warranty only that this product is free of defects, since many factors which affect the results obtained from this product—such as weather, workmanship, equipment utilized, and prior condition of the substrate—are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES:** The Limited Warranty is **IN LIEU OF** any other warranties express or implied including but not limited to any implied warranty of **MERCHANTABILITY** or fitness for a particular purpose, and we, the manufacturer, shall have no further liability of any kind including liability for consequential or incidental damages resulting from any defects or any delays caused by replacement or otherwise.