

# MATERIAL SAFETY DATA SHEET



PROSOCO, Inc.

## I PRODUCT IDENTIFICATION

**MANUFACTURER'S NAME AND ADDRESS:** PROSOCO, Inc.  
3741 Greenway Circle  
Lawrence, Kansas 66046

**EMERGENCY TELEPHONE NUMBERS:**  
**8:00 AM – 5:00 PM CST Monday-Friday:** 785/865-4200  
**NON-BUSINESS HOURS (INFOTRAC):** 800/535-5053

**PRODUCT TRADE NAME:** Consolideck<sup>®</sup> DuraSheen

## II HAZARDOUS INGREDIENTS

CHEMICAL NAME	(COMMON NAME)	CAS NO.	HMIS CODE	ACGIH TLV/TWA	OSHA PEL/TWA
Aromatic Hydrocarbon Solvent	Aromatic 100	64742-95-6	1,2,0,-	NA	NA
Trimethylbenzene	(Component of Stoddard Solvent)	95-65-6	2,2,0,-	25 ppm	25 ppm
Xylene	(Component of Aromatic 100)	1330-20-7	2,2,1,-	100 ppm	100ppm
Petroleum Distillates	(Stoddard Solvent)	8052-41-3	1,2,0,-	100 ppm	500 ppm

## III PHYSICAL DATA

	BOILING POINT (°F)	VAPOR PRESSURE (mm Hg)	VAPOR DENSITY (Air = 1)	EVAPORATION RATE (Butyl Acetate = 1)
Aromatic Hydrocarbon Solvent	318-338	2.1 (68°F)	ND	0.3
Petroleum Distillates	302-392	5.0 (77°F)	4.8	0.08

  

	SPECIFIC GRAVITY	SOLUBILITY IN WATER	APPEARANCE AND ODOR
<b>DuraSheen*</b> *Typical	0.77	Not Soluble	Clear liquid, aromatic odor

## IV FIRE AND EXPLOSION HAZARD DATA

### EMERGENCY OVERVIEW

**Consolideck<sup>®</sup> DuraSheen** is a clear, colorless combustible liquid. May release vapors that form flammable mixtures at or above the flash point. Eliminate potential sources of ignition. Aspiration hazard if swallowed. May cause irritation to the eyes, nose, throat and lungs. May cause headaches and dizziness or other central nervous system effects. Always wear appropriate personal protective equipment when using this product.

**FLASH POINT (METHOD):** 106°F TCC

**FLAMMABLE LIMITS:** ND

**AUTO IGNITION TEMPERATURE:** ND

**EXTINGUISHING MEDIA:** Use water spray to cool fire exposed surfaces and to protect personnel. Use foam, or dry chemicals to extinguish fire.

**SPECIAL FIRE FIGHTING PROCEDURES:** Do not enter confined fire space without proper protective equipment; including a NIOSH/MSHA approved self-contained breathing apparatus. Cool fire exposed containers, surrounding equipment and structures with water.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Vapors are heavier than air and may accumulate in low areas or areas inadequately ventilated. Vapors may also travel along the ground to be ignited at location distant from handling site; flashback of flame to handling site may occur. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**COMBUSTIBLE!!!** Keep container tightly closed. Isolate from oxidizers, heat, and open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions.

---

## **V HEALTH HAZARD DATA**

---

**PRIMARY ROUTES OF EXPOSURE:** Skin, eyes, inhalation, ingestion.

**CARCINOGEN INFORMATION:**

**MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:** Conditions aggravated may include disorders of the skin, respiratory, and nervous system.

**EFFECTS OF OVEREXPOSURE:** Overexposure and intentional misuse can lead to central nervous system depression producing such effects as headache, dizziness, nausea and loss of consciousness, and even asphyxiation. During normal use and with good ventilation applicators should not be exposed to dangerous or toxic levels of any product component. May cause irritation to the eyes, skin and upper respiratory system.

**EYE CONTACT:** Contact with product or mists may cause irritation to the eye.

**SKIN CONTACT:** Prolonged and repeated liquid contact can cause defatting and drying of the skin, which may result in skin irritation and dermatitis. Liquid or concentrated vapors may also cause burning of skin. May aggravate existing dermatitis.

**INHALATION:** High concentrations or prolonged exposure to lower concentrations may be slightly irritating to mucous membranes. High vapor/aerosol concentrations (greater than approximately 500 ppm, attainable at elevated temperatures well above ambient) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. Liquid or mist contact with mucous membranes may cause burns.

**INGESTION:** Liquid ingestion may result in vomiting; aspiration of liquid into the lungs must be avoided as liquid contact with the lungs can result in chemical pneumonitis and pulmonary edema/hemorrhage.

**EMERGENCY AND FIRST AID PROCEDURES:**

**EYE CONTACT:** Remove any contact lenses before beginning to flush eyes. If in eyes, flush with large amounts of water, holding eyelids apart to ensure flushing of the entire eye surface. Get medical attention.

**SKIN CONTACT:** Remove affected person from source of contamination. Wash with soap and water. Remove contaminated clothing and do not reuse until laundered. If irritation occurs, get medical attention.

**INHALATION:** Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

**INGESTION:** DO NOT INDUCE VOMITING even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs, which can cause chemical pneumonitis, which can be fatal. Rinse mouth thoroughly. Get immediate medical attention.

---

## VI REACTIVITY DATA

---

**STABILITY:** Stable.

**CONDITIONS TO AVOID:** Heat, sparks, open flame, moisture.

**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents, concentrated nitric and sulphuric acids, halogen, and molten sulphur.

**HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS:** None

---

## VII SPILL OR LEAK PROCEDURES

---

**EXPOSURE CONTROLS:** The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures, or is agitated.

**SPILL, LEAK, WASTE DISPOSAL PROCEDURES:** STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate potential sources of ignition. Wear appropriate respirator and other protective clothing. Shut off source of leak only if safe to do so. Dike and contain to prevent migration to soil and drains. Remove with explosion-proof equipment. Soak up residue with a noncombustible absorbent such as clay or vermiculite; place in drums for proper disposal.

**WASTE DISPOSAL METHODS:** Product is classified as a hazardous waste under USEPA regulations for the characteristic of ignitability. Dispose of in a facility approved under RCRA regulations for hazardous waste. Containers must be leak-proof and properly labeled.

---

## VIII SPECIAL PROTECTION INFORMATION

---

**RESPIRATORY PROTECTION:** If the recommended exposure limit is exceeded, a NIOSH approved respirator is advised in absence of proper environmental control. Engineering or administrative controls should be implemented to reduce exposure.

**VENTILATION:** Provide sufficient general and/or local exhaust ventilation to maintain exposure below recommended exposure limit. Use explosion-proof ventilation as required to control vapor concentrations below the TLV(s).

**PROTECTIVE CLOTHING:** Wear protective clothing as required to prevent skin contact.

**PROTECTIVE GLOVES:** Wear solvent-resistant gloves, such as nitrile rubber, as required to avoid skin contact.

**EYE PROTECTION:** Chemical splash goggles in compliance with OSHA regulations are advised. Do not wear contact lenses because they may contribute to the severity of an eye injury. Safety glasses with side shields may be appropriate depending on application methods and jobsite conditions.

**OTHER PROTECTIVE EQUIPMENT:** Solvent-resistant boots and headgear as needed depending on application methods and jobsite conditions. Safety shower and eyewash should be accessible to work area.

---

## I SPECIAL PRECAUTIONS

---

**WORK PRACTICES:** Proper work practices and planning should be utilized to avoid contact with workers, passersby, and non-masonry surfaces. Do not atomize during application. Beware of wind drift. See the Product Data sheet and label for specific precautions to be taken during use. **This product is combustible!** Do not apply to heated surfaces. Eliminate all sources of ignition, even remote sources, as vapors may travel some distance. Smoking, eating and drinking should be prohibited during the use of this product. Wash hands before breaks and at the end of a shift.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store away from alkalis and oxidizing materials in a cool, dry place with adequate ventilation. Keep away from heat and open flames. Keep container tightly closed when not dispensing product. Bond and ground containers during transfer to avoid electrostatic accumulation.

Wash up with soap and water before eating, drinking, smoking or using toilet facilities. Launder contaminated clothing before reuse.

Containers of this material may be hazardous when emptied, since emptied containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given in the Data sheet must be observed.

**OTHER PRECAUTIONS:** Environmental Hazards - Keep out of surface water and watercourses or sewers entering or leading to surface waters.

---

## X REGULATORY INFORMATION

---

**SHIPPING:** Product carries the proper shipping description "**Resin Solution, 3, UN1866, III**" for domestic and international transport. For domestic ground shipping, USDOT exempts combustible liquids if under 119 gallons per container. The alternate shipping description is "NON-HAZARDOUS/NON-REGULATED (UNDER 119 GALLONS PER CONTAINER)". Certain container and packaging combinations are restricted in shipment by air and by parcel carriers.

**NATIONAL MOTOR FREIGHT CLASSIFICATION:** NMFC#: 48580 Sub 3 Class Rate: 55

**SARA 313 REPORTABLE:**

CHEMICAL NAME	CAS	UPPERBOUND CONCENTRATION % BY WEIGHT
Trimethylbenzene	95-63-6	10.0%
Xylene	1330-20-7	5.0%

**CALIFORNIA PROPOSITION 65:** Does not contain chemicals listed under California's Proposition 65.

---

## XI OTHER

---

**MSDS Status:**           **Date of Revision:** June 8, 2005  
**For Product Manufactured After:** May 31, 2005  
**Changes:** Revised Shipping Description, Section X  
**Item #:** 40032  
**Approved By:** Regulatory Department

---

## DISCLAIMER:

The information contained on the Material Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. **PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described.** This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

**DATE OF PREPARATION:** June 8, 2005