

GOLD LABEL 1P LOOP SEALANT

Version 2.1

06/28/2006

1. PRODUCT AND COMPANY INFORMATION

Company	:	BASF Building Systems 889 Valley Park Drive Shakopee, MN 55379
Telephone	:	952-496-6000
Emergency telephone number	:	(800) 424-9300 (703) 527-3887 (Outside Continental US)
Product name	:	GOLD LABEL 1P LOOP SEALANT
MSDS ID No.	:	10725
TSCA Inventory	:	All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
Canadian DSL	:	All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).
Product Use Description	:	Sealant

2. HAZARDOUS INGREDIENTS

<u>Chemical</u>	<u>CAS No.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	<u>Weight %</u>
POLYVINYL CHLORIDE	9002-86-2	1 ppm	5 ppm	N.E.	N.E.	15.00 - 40.00 %
XYLENE	1330-20-7	100 ppm	150 ppm	100 ppm	300 ppm	10.00 - 30.00 %
TOLUENE DIISOCYANATE MIX	26471-62-5	0.005 ppm	0.02 ppm	N.E.	N.E.	0.00 - 2.00 %

3. HAZARDS IDENTIFICATION

HMIS [®] Rating	HEALTH	FLAMMABILITY	PHYSICAL HAZARD
	2*	3	0
WHMIS Class	:	B2	
Primary Routes of Entry	:	Ingestion Inhalation Eye contact Skin contact	

Effects of Overexposure

Inhalation	:	Harmful by inhalation. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing.
Skin	:	Prolonged skin contact may defat the skin and produce dermatitis. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact.

GOLD LABEL 1P LOOP SEALANT

Version 2.1

06/28/2006

- Eyes : Can cause slight to moderate irritation, redness, tearing and blurred vision.
- Ingestion : Intake can cause gastrointestinal irritation, nausea, and vomiting. Moderate toxicity.
- Chronic exposure : Chronic overexposure to xylene can cause damage to the formed elements of blood [e.g., red cells, which carry oxygen]. This product contains solvents. Reports associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Reports also indicate that solvents cause liver damage, kidney damage, and mucous membrane irritation. Be warned that intentional misuse by deliberately inhaling the vapors and/or the product contents (a process often called "sniffing") can be harmful or fatal. Existing respiratory or skin ailments may be aggravated by exposure. This product contains isocyanates. Prolonged repeated exposure to isocyanates can lead to skin sensitization. For persons so sensitized even brief exposures to an isocyanate can produce reddening, swelling, rash, or blisters. Similarly, prolonged and repeated exposure to isocyanates can lead to respiratory sensitization. In such individuals, brief exposures to isocyanates at levels well below established exposure limits can produce chemical asthma and nonspecific asthmatic conditions.

Carcinogenicity

	ACGIH	IARC	NTP	OSHA
POLYVINYL CHLORIDE	N.E.	Inadequate data.	N.E.	Potential cancer hazard.
XYLENE	Not classifiable as a human carcinogen.	Classification not possible from current data.	N.E.	N.E.
TOLUENE DIISOCYANATE MIX	Sensitiser.	No data.	Anticipated carcinogen.	N.E.

4. FIRST AID MEASURES

- Eye contact : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
- Skin contact : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
- Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.
- Inhalation : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

5. FIRE-FIGHTING MEASURES

- Flash point : 93.00 °F (33.89 °C) Method: Taglibue C. C.
- Autoignition temperature : 870.01 °F (465.56 °C)
- Lower explosion limit : 1.1 %(V)

GOLD LABEL 1P LOOP SEALANT

Version 2.1

06/28/2006

Upper explosion limit	:	6.6 %(V)
Suitable extinguishing media	:	carbon dioxide (CO ₂) foam dry chemical water fog
Fire and Explosion Hazards	:	Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; CONTAINERS MAY EXPLODE AND CAUSE INJURY OR DEATH. Heating can release vapours which can be ignited. Solid stream of water or foam can cause frothing.
Special Fire-fighting Procedures	:	Can be ignited by heat, sparks or flame. At higher temperature pressure build up in sealed containers. Use water to cool containers exposed to fire. As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up	:	Ventilate the area and remove all sources of ignition. Evacuate unnecessary personnel. Take action to eliminate source of leak. Large spills should be handled carefully. Put on respiratory protection and necessary personal protective equipment. Dike or impound spilled Liquid. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-------------------------	---	--

7. HANDLING AND STORAGE

Handling	:	Keep out of reach of children. Use only in area provided with appropriate ventilation. Take precautionary measures against static discharges. Ground and bond containers when transferring material. For personal protection see section 8.
Storage	:	Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye protection	:	Wear as appropriate: safety glasses with side-shields goggles face-shield
Hand protection	:	Wear Chemically resistant gloves.
Body Protection	:	Wear as appropriate: Chemically resistant clothes preventive skin protection

GOLD LABEL 1P LOOP SEALANT

Version 2.1

06/28/2006

- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.
- Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.
- Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Color : no data available
- Physical State : paste
- Odor : solvent
- pH : not applicable
- Odor Threshold : no data available
- Vapor Pressure : 9 mm/Hg at 77 °F (25 °C)
- Vapor Density : 3.7 (Air = 1)
- Boiling point/range : 278.01 - 289.99 °F (136.67 - 143.33 °C)
- Freeze Point : no data available
- Water solubility : insoluble
- Specific Gravity : 1.09
- Viscosity : no data available
- Evaporation rate : Slower than ether
- Partition coefficient (n-octanol/water) : no data available
- VOC Concentration as applied (less water and exempt solvents) : 187 g/l

10. STABILITY AND REACTIVITY

- Stability : Stable under recommended storage conditions.
- Conditions to avoid : Heat, flames and sparks.
Direct sources of heat.

GOLD LABEL 1P LOOP SEALANT

Version 2.1

06/28/2006

Strong sunlight for prolonged periods.
Prolonged exposure to high temperatures

- Materials to avoid : Water
- Hazardous decomposition products : Oxides of carbon
Thermal decomposition can lead to release of irritating gases and vapours.
- Hazardous polymerization : Will not occur under normal conditions.

11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>	<u>Exposure time</u>
	LC50	no data available		
<u>Component</u>				
POLYVINYL CHLORIDE	LC50	no data available		
XYLENE	LC50	no data available		
TOLUENE DIISOCYANATE MIX	LC50	no data available		

Acute oral toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Oral)	no data available	
<u>Component</u>			
POLYVINYL CHLORIDE	LD50 (Oral)	no data available	
XYLENE	LD50 (Oral)	4,300 mg/kg	rat
TOLUENE DIISOCYANATE MIX	LD50 (Oral)	4,130 mg/kg	rat

Acute dermal toxicity

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Dermal)	no data available	
<u>Component</u>			
POLYVINYL CHLORIDE	LD50 (Dermal)	no data available	
XYLENE	LD50 (Dermal)	> 1,700 mg/kg	rabbit
TOLUENE DIISOCYANATE MIX	LD50 (Dermal)	1,950 mg/kg	

GOLD LABEL 1P LOOP SEALANT

Version 2.1

06/28/2006

12. ECOLOGICAL INFORMATION

Ecotoxicological Information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

14. TRANSPORT INFORMATION

DOT	: Proper shipping name	RESIN SOLUTION
	UN-No	1866
	Class	3
	Packaging group	III
IATA	: Proper shipping name	RESIN SOLUTION
	UN-No	1866
	Class	3
	Packaging group	III

15. REGULATORY INFORMATION

SARA 311/312 (RTK)

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

FIRE HAZARD IMMEDIATE (ACUTE) HEALTH HAZARD DELAYED (CHRONIC) HEALTH HAZARD

SARA 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Weight %</u>	<u>CAS No.</u>	<u>Chemical Name</u>
10.00 - 30.00 %	1330-20-7	XYLENE
0.00 - 2.00 %	26471-62-5	TOLUENE DIISOCYANATE MIX

CERCLA

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
100 lbs	1330-20-7	XYLENE
100 lbs	26471-62-5	TOLUENE DIISOCYANATE MIX

TSCA Section 12(b) Export Notification

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from

GOLD LABEL 1P LOOP SEALANT

Version 2.1

06/28/2006

the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no TSCA 12(b) Chemicals in this product.

California Proposition 65

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

<u>CAS No.</u>	<u>Chemical Name</u>
26471-62-5	TOLUENE DIISOCYANATE MIX

16. OTHER INFORMATION

Legend : N.E. - Not Established
TLV - Threshold Limit Value
STEL - Short Term Exposure Limit
PEL - Permissible Exposure Limit
CEIL - Ceiling

Prepared By : Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.