

Diamond[®]

For residential and light commercial wall projects, Diamond[®] blocks feature patented rear-lip technology for a uniform setback and quick installation. Easy-to-install Diamond blocks are available in straight- or beveled-faced styles in a variety of natural colors. Optional step and cap accessories offer even more design versatility.



Anchor[®]
RETAINING WALL SYSTEMS
1-877-295-5415
www.anchorwall.com

Diamond[®]

The classic Diamond[®] block is the contractor's choice for wall construction. The integral rear lip speeds installation, eliminates guesswork and reduces labor costs with a quick, uniform setback. You can build gravity walls up to four feet high (1.2 m) or, with geosynthetic reinforcement and professional design, Diamond walls can reach heights in excess of 30 feet (10 m). Straight or beveled face styles provide more design freedom. For an attractive retaining wall with enduring performance, Diamond is the perfect choice.



No pins. No mortar. No misalignments. Our patented rear-lip technology makes installation quick, efficient and accurate. Anchor – the original rear-lip product!

Specifications



Units	Beveled Face	Straight Face
Nominal Dimensions*	6' x 15 1/2" x 12" [150 mm x 400 mm x 300 mm]	6' x 17 1/2" x 12" [150 mm x 435 mm x 300 mm]
Approx. Weight	68 lbs. (31 kg)	72 lbs. (33 kg)
Coverage	.67 sq. ft. (0.065 m ²)	.72 sq. ft. (0.065 m ²)
Setback	1 1/2" (30 mm)	1 1/2" (30 mm)
Batter	10.6°	10.6°
Minimum Inside Radius	4 feet (1.2 m)	8 feet (2.4 m)
Minimum Outside Radius	2 feet (600 mm)	4 feet (1.2 m)



Accessories	Cap	Step
Nominal Dimensions*	3' x 17 1/2" x 10" [75 mm x 435 mm x 250 mm]	6' x 16" x 12" [150 mm x 400 mm x 300 mm]
Approx. Weight	32 lbs. (15 kg)	85 lbs. (39 kg)

*Nominal Dimensions. Actual dimensions and weight may vary from these nominal dimensions due to variations in manufacturing processes. Specifications may change without notice. See your Anchor representative for details, color options, block dimensions and additional information.



In the United States, Anchor Wall Systems products are backed by a Limited Warranty. For a complete copy of the Anchor Wall Systems Warranty, visit your local distributor or manufacturer or contact Anchor Wall Systems at 1-877-293-5413 or www.anchorwall.com. ©2006 Anchor Wall Systems, Inc. 5030 Baker Road, Suite 390, Minneapolis, MN 55345-5905 USA. For more information call us toll-free in the U.S. at 1-800-473-4492. Outside the U.S. call +1-952-433-9925 or visit www.anchorwall.com.

Anchor Wall Systems, Diamond and the Anchor W logo are trademarks of Anchor Wall Systems, Inc. Diamond is manufactured only by licensed Anchor Wall Systems producers as protected by U.S. Patent Nos. 6,294,216; 6,827,015; 6,142,712; 6,143,148; 6,312,197. Other U.S. and International patents issued and pending.